FD511G-F660

1GE XPON ONU

High Speed CPU


Low Power Consumption


Software Customization

Optional Shell Supply

Brief Views

FD511G-F660 is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16/17 series GPON OLT or FD13 / 12 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet service based on GPON and EPON technology.






Functional Feature

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support VLAN transparent/tag/translate/trunk
- Single-fiber access, provides internet multiple service.
- Support broadcasting storm resistance function
- Support Dynamic Bandwidth Allocation (DBA)
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function ,easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support remote WEB/Telnet access control

Product Interface and LED





LED Definitions

Indicator		Description
PWR	Power status	On: The ONT is power on; Off: The ONT is Power off;
PON	ONT Register	On: Success to register to OLT; Blinking: In process of registering to OLT; Off:Failed to register to OLT or no normal optical signal input;

LOS	PON optical signals	On: Optical power lower than receiver sensitivity; Off: Optical in normal;
LAN	LAN port status	On: Ethernet connection is normal; Blinking: Data is being transmitted through the Ethernet port; Off: Ethernet connection is not set up;

Product Specification

Mechanics	
Dimensions	78mm(L) x78mm(W) x23.5mm (H)
Weight	About 62.7g

Hardware			
User Port (LAN)		RJ-45 connector	
		1*10/100/1000Mbps adaptive Ethernet port	
		Full/half duplex	
		Auto MDI/MDI-X	
Indicators		PWR / PON / LOS / LAN	
PON Port	PON Mode	EPON：1000BASE-PX20+ symmetric GPON： FSAN G.984.2 standard,Class B+	
	PON Rate	EPON：1.25Gbps downstream/upstream GPON： 2.488Gbps/1.244Gbps downstream/upstream	
	Wavelength	Transmit: 1310nm	Receiver: 1490nm
	Receiving sensitivity	EPON：-27dBm	GPON：-28dBm
	Saturated power	EPON：-3dBm	GPON：-8dBm
	Transmitting power	EPON:0～4dBm	GPON：0.5～5dBm

Environment	
Working temperature	0 to 40° C
Operating humidity	10% ~ 90% (Non-condensing)

Power	
External 12V/0.5A DC power supply adapter	
Power consumption	<3W

Copyright © Shenzhen C-Data Technology Co., Ltd. 2023. All rights reserved.

Without the prior written consent of C-DATA, any reproduction, excerpting, backup, modification, translation or any other form of commercial use of this document or any portion of this document, and in any form or by any means, to transmit the document are prohibited.